

# MATERIAL SAFETY DATA SHEET

---

## Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

---

	DATE OF PREPARATION	HMIS CODES	
PRODUCT NUMBER		Health	0
7601/ Flat , 7602/ Gloss	1 January 15	Flammability	0
		Reactivity	0

### PRODUCT NAME

Plastic Varnish Clear Water Reducible Coating  
Flat & Gloss

### MANUFACTURER'S NAME

Sculptural Arts Coating, Inc.  
1200 Forest Hill Drive  
Greensboro, NC 27410

### EMERGENCY TELEPHONE NUMBER

(336) 851-0355

### INFORMATION TELEPHONE NUMBER

(336) 851-0355

---

## Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

---

% by WT	CAS No.	INGREDIENT	UNITS	VAPOR PRESSURE
---------	---------	------------	-------	----------------

---

No information is required here.

---

## Section 3 -- HAZARDS IDENTIFICATION

---

### ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.

EYE or SKIN contact with the product, vapor or spray mist.

### EFFECTS OF OVEREXPOSURE

EYES: Irritation.

SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.

In a confined area vapors in high concentration may cause headache, Nausea or dizziness.

continued on page 2

---

**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**

None generally recognized.

---

**Section 4 - - FIRST AID MEASURES**

---

**EYES:** Flush eyes with large amounts of water for 15 minutes.  
Get medical attention.

**SKIN:** Wash affected area thoroughly with soap and water.  
Remove contaminated clothing and launder before re-use.

**INHALATION:** If affected, remove from exposure. Restore breathing.  
Keep warm and quiet.

**INGESTION:** Do not induce vomiting.  
Get medical attention immediately.

---

**Section 5 - - FIRE FIGHTING MEASURES**

---

<b>FLASH POINT</b>	<b>LEL</b>	<b>UEL</b>
Not applicable	N.A.	N.A.

**FLAMMABILITY CLASSIFICATION**

Not applicable

**EXTINGUISHING MEDIA**

Carbon Dioxide, Dry Chemical, Alcohol Foam

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers may explode (due to the build up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**SPECIAL FIREFIGHTING PROCEDURES**

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

---

**Section 6 - - ACCIDENTAL RELEASE MEASURES**

---

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

continued on page 3

---

---

**Section 7 - - HANDLING AND STORAGE**

---

**STORAGE CATEGORY**

Not applicable

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

---

**Section 8 - - EXPOSURE CONTROLS/ PERSONAL PROTECTION**

---

**PRECAUTIONS TO BE TAKEN IN USE**

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

**VENTILATION**

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits.

Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION**

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint or the abrasive.

**PROTECTIVE GLOVES**

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

continued on page 4

**EYE PROTECTION**

Wear safety spectacles with unperforated sideshields.

---

**Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES**


---

PRODUCT WEIGHT 8.8 - 9.0 lb. / gal.

BOILING POINT 212 - 213 F

VOLATILE VOLUME 68%

EVAPORATION RATE Slower than ether

VAPOR DENSITY Heavier than air

VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)  
 <= 50 g/l Less Water and Federally Exempt Solvents

---

**Section 10 -- STABILITY AND REACTIVITY**


---

STABILITY -- Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur.

---

**Section 11 -- TOXICOLOGICAL INFORMATION**


---

No ingredient in this product is an IARC, NTP, or OSHA listed carcinogen.

---

**TOXICOLOGY DATA**


---

CAS No.	Ingredient Name
---------	-----------------

No data given.

continued on page 5

---

 Section 12 - - ECOLOGICAL INFORMATION
 

---

 ECOTOXICOLOGICAL INFORMATION
 

---

No data available.

---

 Section 13 - - DISPOSAL CONSIDERATIONS
 

---

 WASTE DISPOSAL METHOD
 

---

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate in approved facility. Do not incinerate closed container.  
Dispose of in accordance with Federal, State/ Provincial, and Local regulations regarding pollution.

---

 Section 14 - - TRANSPORT INFORMATION
 

---

 US Ground (DOT)
 

---

Not Regulated for Transportation.

 Canada (TDG)
 

---

Not Regulated for Transportation

---

 Section 15 - - REGULATORY INFORMATION
 

---

 SARA 313 (40 CFR 372.65 C) SUPPLIER NOTIFICATION
 

---

CAS No.	CHEMICAL / COMPOUND	% by WT	% Element
---------	---------------------	---------	-----------

---

No ingredients in this product are subject to SARA 313 (40 CFR 372.65 C) Supplier Notification.

 TSCA CERTIFICATION
 

---

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

---

 Section 16 - - OTHER INFORMATION
 

---

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The information contained herein is based on data available to us. However, no warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from the use thereof. Since the use of this information and the conditions of the use of the product are not under our control, it is the user's obligation to determine conditions of safe use of this product and we assume no liability in connection with the use of this information.